

Hydraulic Ironworker Model AIW-65



CAPACITIES:

Punching: 65 tons
(1 1/8" x 5/8")

Shearing:

Flat bar (thick): 9 3/4 x 9/16"
Flat bar (large): 15 x 5/16"

Round bar: 1 9/16"
Square bar: 1 3/8"

Angle iron (90°): 4 x 4 x 7/16"
Angle iron (45°): 2 x 2 x 5/16"

T-Shape bar: 4 3/4 x 7/16

I-Beam: 4 7/8 x 2 7/8 x 3/16"

Channels: 4 7/8 x 2 x 3/16"

STANDARD EQUIPMENT:

- Removable halogen light
- High-capacity hydraulic tank
- Safety guards for all stations
- Durable, standardized welded structure
- Adjustable electric gauge for cutting stations
- Hydraulic foot switch for cutting (130T and +)
- Adjustable guide table for clamping station
- Adjustable guide table for punching station
- Dual operator operation possible (dual station)
- Set of ten (10) drill punches and dies
- Laser Alignment Beam for Punching Station
- High strength knives for long life
- Several options available for specific uses
- Foot switch for cutting (95T and -, hydraulic optional)
- Easy adjustment of punch stroke and other stations
- Electrical/hydraulic components selected for reliability

Throat depth (punching):	11,8" (300 mm)
Stroke (folding):	3.18" (80 mm)
Speed (hits/min):	8-22 (according to adjusted stroke)
Oil tank volume (litres):	170
Main motor:	7,5 HP, 575V/3ph/60hz
Overall dimensions:	71"(L) x 35"(W) x 71"(H)
Approximate weight:	3,960 lbs.

Productive;

Polyvalent;

Reliable; and

Affordable

